









Touch Performance

- Sealed glass front (water and dust resistant)
- Easy to clean
- Ultra Fast Precision Touch Response
- Requires human intentional touch (HIT)
- USB HID compliant, driver-free with no calibration
- Anti-Glare - Diffuses mirror-like reflection
- Touch operation is unaffected by surface contaminants

Sizes: 32", 42", 46", 55" & 65"

 Reliability	 Anti Fingerprint	 Plug & Play	 Easy Cleaning	 Sealed Glass Front	 Fast Response
---	---	--	--	---	--

Epic-Series LED Multi-Touch PCAP Touch Screen

SPECIFICATIONS

Part #	EPC321	EPC421	EPC461	EPC551	EPC651
Touch Interface:	Projected Capacitive 10 Point Multi-Touch (Finger, Capacitive Stylus, Nitrile, Latex and Vinyl Gloves)/ USB				
Active Screen Area	27.5 x 15.5in	36.6 x 20.6in	40 x 22.5in	47.6 x 26.8in	56.2 x 31.6in
Aspect Ratio	16:9				
Brightness:	450	350		500	
Contrast Ratio	3000:1			4000:1	
Viewing Angle	178° Vert., 178° Hor.				
Response Time	Rapid Response (6.5ms)				
Color Depth	16.7 Million Colors				
Pixel Pitch	.364mm	.485mm	.530mm	.63mm	.74mm
Native Resolution	1920 x 1080 HD @ 60 Hz				
Inputs	HDMI, DVI and VGA/ Audio In/ Out				
Power Consumption	68W	90W	95W	105W	120W
Power Supply	Internal power switching AC 100V~240V				
Dimensions (WxHxD)	31.1 x 19.2 x 2.3in	40.4 x 24.4 x 2.6in	43.9 x 26.4 x 2.7in	51.6x 30.8 x 2.7in	56.2 x 31.6 x 2.7in
VESA Specification	400mm x 300mm	600mm x 400mm	400mm x 400mm	400mm x 400mm	400mm x 400mm
Weight	39 lbs.	57 lbs.	66 lbs.	95 lbs.	132 lbs.
Temperature	Operating 0 - 104°F / Storage -4°F - 140°F				
Humidity	Operating 20% - 80% / Storage 10% - 90%				
Warranty	2 Years				

